AIP Conference Proceedings

RESEARCH ARTICLE | JANUARY 30 2023

# Creating a cost-effective network of operational resources for wireless networks

Venkateshwara Prasad ✉; Bhadrappa Haralayya; R. Aruna Jayashree; ... et. al

Check for updates

*AIP Conference Proceedings* 2523, 020087 (2023)
https://doi.org/10.1063/5.0110970

View Online
Export Citation
CrossMark

## Articles You May Be Interested In

Sound source ranging using a feed-forward neural network trained with fitting-based early stopping

*J Acoust Soc Am* (September 2019)

Development of intelligent instruments with embedded HTTP servers for control and data acquisition in a cryogenic setup—The hardware, firmware, and software implementation

*Rev Sci Instrum* (December 2015)

We'd like to know how we're doing and where we're going!

*The Physics Teacher* (September 2020)

Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

AIP Publishing

# Creating a Cost-Effective Network of Operational Resources for Wireless Networks

Venkateshwara Prasad[1,a)], Bhadrappa Haralayya[2b)], R Aruna Jayashree[3c)], A. Kethsy Prabavathy[4d)], S. Selvarasu[5e)]

[1]*Department of Management Studies, Sri Sairam Engineering College, Chennai, Tamil Nadu, India.*
[2]*Department of Management Studies Lingaraj Appa Engineering College Bidar, Karnataka, India.*
[3] *Department of Electronics and Communication Engineering, Rajalakshmi Institute of Technology, Chennai, Tamil Nadu, India.*
[4]*Department of Computer Science and Engineering, Karunya Institute of Technology and Sciences, Coimbatore, Tamil Nadu, India.*
[5] *Department of Electronics and Communication Engineering, Muthayammal Engineering College, Tamil Nadu, India.*

Corresponding Author Email: [a)]bvprasad.mba@sairam.edu.in
[b)]bhadrappabhavimani@gmail.com
[c)]arunajayashree@gmail.com
[d)]kethsypraba@gmail.com
[e)]selvarasumec@gmail.com

**Abstract.** Wireless Sensor Networks (WSNs) gives human civilization a stunning and clever landscape. Connections between different sensors also strategies in the Internet of Things (IoT) contribute to high energy feasting. Study into liveliness conservation and methods of energy-saving are also important. Sustainability in an energy-efficient way due to the sensors' partial power is important for wireless sensors in an IoT network. This paper aims to analyze an IoT network of remote monitoring and access points. Wireless battery charging power delivery methods are getting more mature. The electrical power supply is operated by a charging car for wireless sensors. The data sharing of the IoT network situation is a minimization challenge to conserve electric energy. A three-stage process obtains the solution. A Reboot Artificial Bee Community (RABC) approach is proposed to solve the sub-problems of the data transfer model. The RABC approach has been shown to converge asymptotically to the optimization process. Computer modelling demonstrates that energy consumption can be reduced with a strong, robust function using the proposed approach in the intentional network scenario.

**Keywords:** Reboot Artificial Bee Community, Wireless Sensor Networks, Internet of Things, battery charging power delivery, optimization process, and robust function.

## INTRODUCTION

Network adapter is an Internet-based network. "Stuff" and the Internet interact in line with a certain arrangement to share and communicate information through radio frequency identifying devices and sensors and positioning devices to improve the intelligence of identification, location, and surveillance of the object. Its most important function is connectivity and dialogue between objects, which can also connect with the environment [1-2].

In 2003, United States Scientific Comments suggested that the sensor communication system would become the first technology to improve human lives. The MIC of Japan suggested the 2004 project U-Japan to link individuals, things, objects, items, and the like. It sought to make Japan a networked community at any time, whenever, between everything and everybody [3]. During the 2005 World Summit on Information Society detained in Tunisia, the Telecommunication Standardization Union (ITU) unconfined "ITU Internet Study 2005: Stuff." The "Internet of Things" definition is described in this paper. The IoT's spectrum has been extended enormously, with little relation

*Recent Advancement In Mechanical Engineering And Industrial Management*
AIP Conf. Proc. 2523, 020087-1–020087-6; https://doi.org/10.1063/5.0110970
Published by AIP Publishing. 978-0-7354-4301-3/$30.00



Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

to the Internet of RFID-based things [4]. In 2008 in China, Invention 2.0 was proposed to grow the smartphone and IoT innovations, which developed a new information security age and encouraged economic and social development through creative shapes. In 2009, IoT was a crucial influence in the revitalization of America's economy.
IoT has received global recognition and has quickly grown. In several years from 2010 to 2013, the number of interconnected computers worldwide rose from 7 billion to 9 billion. By 2020, 24 billion smartphones are expected to launch. According to the Mobile Networks Alliance Global Structure, it is worth $1.3 trillion in income to hospitals, automotive, public services, and consumer electronics mobile network operators [5].




**FIGURE 1.** A wireless Sensor network model

To create IoT, all wireless connection sensors, as well as other sensors, need to be connected. Wireless sensors typically have low-capacity batteries. The restricted power restricts the transmission of data in the IoT [6]. Thus, it is unavoidable that an energy-efficient process should promote IoT production. This paper aims to analyze an IoT situation of wireless sensor nodes and bases. Figure 1 illustrates the wireless network model. This figure contains micro bases station (BS), macro BS, and nodes. Wireless sensors produce and communicate data to BSs. Two BSs layers are established: the micro BS and the macro BS. The Micro BS collects information besides transfers it to the BS macro from the wireless sensors. The BS Macro then transfers information to the cloud computing network or database. The wireless power-sharing strategy is ideal for battery charging with respect to reduced battery space. The sensors' battery charge is believed to be charged by a vehicle with a large battery capacity. To address the file transfer issues, a conceptual framework is proposed [7].

## LITERATURE SURVEY

There are five innovations in the IoT: RFID, WLAN, web services, cloud storage, and IoT device soap [8-9]. There are no other systems used in this market. The WSN contains the essential technologies for the collection of environmental data and data. A wireless sensor system is a processer system that uses independent spatially dispersed strategies to track the conservational and demographic status of the various positions, including weather, sounds, movement, vibration, etc. WSN technology has recently been extensively used for industrial regulation, smart houses, defence, military security, smart agricultural, environment protection, and health surveillance [10].

The WSN can be modelled as optimization problems to synchronize or find and then solved using nonlinear programmes. The battery capacity they carry is restricted since of the sensor nodes' limited capacity and hence limits the usage of the WSN [11]. Researchers developed energy exchangeable routing protocols to address the liveliness issue to tackle this problem. However, these experiments could only minimize power usage and did not fill the nodes without energy. Thus, wireless power transfer technology offers the ability to refill the sensor at any time with electricity [12].

The research team suggested the wireless power transmission technology based on coupling magnet resonance from MIT in 2007. In this method, the power will wirelessly be transmitted from the transmitter belt to the receiver



Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

belt with the same resonant frequencies. The wireless communication system based on combined magnetic resonances transfers' power over medium distances at great performance, as opposed to the inductive wireless power transmission system [13]. Zhang et al. explored the charging issue using a plate structure near the Ground in the WPT method. Zhao et al. analyzed the time allocation for a 3-node WPT coordination device Rana and Xiang's evaluation and IoT network stability with regards to the WPT scheme.

The Wireless Network of Rechargeable Sensors (WRSN) is developed and analyzed to integrate the WSN and WPT technology. The purpose of using a mobile charging vehicle [14] is to charge the battery from each sensor. The researchers collected the full holiday period over the cycle of the mobile charging vehicle. To reduce charging delays, Fu et al. recommended charging for WRSNs. The authors did not consider data communication between sensors and ground stations. In [15] suggested a generator algorithm for mutual routing and loading that did not charge the nodes one by one. A Poisson process was updated for ray arrival rate as well as discover which this approach is optimum for modeling ray arrival rate. In addition, Nakagami fading distribution was deliberated in the UWB channel model that outfits for time fluctuating multipath radio situation [16]. A new region-based energy-conscious is used to improve the lifetime applying stable election protocol. It is established on the whole energy of the distinct regions of the whole observing field [17].

## PROPOSED SYSTEM

The situation involves wireless sensor networks, micro-ground stations, also mega-base stations. Wired interface interfaces are additional secure than wireless sensors with a wired sensor or a phone. Wired instruments in this sample are also not included. Wireless instruments have low-capacity batteries. They are expected to have the same battery type and are powered up at first. Two simple stations are available: the BS macro and the BS micro. Wired relations amongst the medium BSs in addition to a macro-BS are expected to occur. Since wireless links are less secure and use more resources than powerline adapters, wireless sensors can make more effort [18].

Availability of mobile features and microscope numbers, respectively, denote NMI and NMI. Imagine that the processing sensor data rate I is Ri. The sensors relay information to the small BSs, which transfers information to the BS macro. If a BS microphone does not assist a device, the closest sensor is a transmission relief. In such a scenario, the multi-hop transfer of data may be necessary. Therefore, data sent, obtained, and sent via sensor I must be matched. Several methods exist to find the shortest circuit of Hamilton. A new method for this problem will be established in the following section.

This approach is more efficient than other methods but, therefore, more stable. Second, the disturbance area for each node can be calculated. Due to its small transmitting capability and micro-BS, its interference area radius can be determined. To make it simpler, wireless sensors are believed to have a similarRws radius, and the micro-BSs have almost a similar RMI radius. If the interfering radius is located at a distance among two nodes, each should use the same channel; otherwise, if the same channel is used, both the nodes interfere.

The second is to eliminate reciprocal node involvement from the graph colouring theory. The graphic colouring theory is very useful to remove reciprocal interference in nodes located within the interference field. The nodes with probable interruption are an isotonic solution. An undirected graph is known to be the coverage area of a micro BS. The reciprocal intervention among two micro-BSs is believed to be missing.

The number of colours is not greater than 5, as per the Headwood Hypothesis. Thus, if the interference with one another can be reduced to a planar graph without a path, five networks are enough to eliminate it. Stage, several uplink paths are possible, particularly when there are a large number of nodes. The optimum or inadequate route should be defined for resource applications. Set parameters and ei should be defined as measured from the model. A second equality constraint can be used to measure parameter ei. Thus, it is important to evaluate the remedy.

First of all, find a range of successful and viable models solutions. Let graph nodes by the sensors and the micro-bps. Then create an arbitrary number of all the nodes through which the data can be distributed based upon enabling interference with two nodes linked by an edge. The minimal span tree can be found after a graph is constructed. Micro-BSs are required to link to the macro-BS, so MSTs for each micro-BS and its respective coverage area should be determined more effectively. Each BS microphone is thus the core of its area. The MST can be found using the approach suggested in the next section. We would then prove that MST-based transfer rate is a viable model approach.

Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

## RESULTS AND DISCUSSIONS

The Figure 2 explains the Routing scenario of WSNs, micro-ground stations (BSs), also a mega-base station. Wired interface interfaces are additional secure than wireless sensors with a wired sensor or a phone. Wired instruments in this sample are also not included. Wireless instruments have low-capacity batteries. They are expected to have the same battery type and are powered up at first. Two simple stations are available: the BS macro and the BS micro. Wired relations between the medium BSs besides a macro-BS are expected to occur. Since wireless links are less secure and use more resources than powerline adapters, wireless sensors can make more effort.




**FIGURE 2.** Routing scenario

Availability of mobile features and microscope numbers situation presents NMI and NMI. Imagine that the processing sensor data rate I is Ri. The sensors relay information to the small BSs, which transfers information to the BS macro. If a BS microphone does not assist an instrument, the closest sensor is a transmission relief. In such a scenario, the multi-hop transfer of data may be necessary. Therefore, data sent, obtained, and sent via sensor I must be matched. Several methods exist to find the shortest circuit of Hamilton. A new method for this problem will be established in the following section.

This approach is more efficient than other methods but, therefore, more stable. Second, the disturbance area for each node can be calculated. Due to its small transmitting capability and micro BS, its interference area radius can be determined. To make it simpler, wireless sensors are believed to have the same Rws radius. Also, the micro BSs have almost a similar RMI radius. If the interfering radius is located at a distance between two nodes, each should use the same channel; otherwise, if the same channel is used, both the nodes interfere.

The second is to eliminate reciprocal node involvement from the graph colouring theory. The graphic colouring theory is very useful to remove reciprocal interference in nodes located within the interference field. The nodes with probable interruption are an isotonic solution. An undirected graph is known to be the coverage area of a micro BS. The reciprocal intervention among two micro-BSs is believed to be missing. The number of colours is not greater than 5, as per the Head wood Hypothesis.

Thus, if the interference with one another can be minimized to a planar graph without a path, five networks are enough to eliminate it. Stage, several uplink paths are possible, particularly when there is a large number of nodes. The optimum or inadequate route should be defined for resource applications. Set specifications and ei should be defined as measured from the model. A second equality constraint can be used to measure parameter ei. Thus, it is important to evaluate the remedy.

First of all, find a range of successful and viable models solutions. Let graph nodes by the sensors and the micro-bps. Then create an arbitrary number of all the nodes through which the data can be distributed based upon enabling interference with two nodes linked by an edge. The minimal span tree can be found after a graph is constructed. Micro-BSs are required to link to the macro-BS, so MSTs for each segment and sub and its respective coverage area should be determined more effectively. Each BS microphone is thus the core of its area. The MST can be found



Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

using the approach suggested in the next section. We would then prove that MST-based transfer rate is a viable model approach.

## CONCLUSION

The whole study explored a wireless sensor also base-stations IoT scenario. Micro-BS collects information also transfers it to a macro-BS from wireless sensors. Then the macro-BS transfers information to a registry or a data centre. The WPT technology is ideal for charging the battery with reduced battery space. An optimization problem is the IoT situation. The model minimizes the grid's electricity consumption. The problem requires a three-stage process. The steps identify the shortest path, decrease shared intervention and decide the best uplink route. To solve the path also uplink route, a restart of the artificial colony of bees is suggested. There is also proof of the asymptotic convergence of the RABC process. Reproductions verify the efficiency of the proposed method. The approach has been shown to solve the IoT network data transmitting problem. A collection of optimum and suboptimal solutions can be accomplished with RABC. This capacity increases the network's robustness toward new incidents. The network's vital nodes are wireless sensors operating like relays. It calls for a secure and robust network of data transmission. The efficiency of power transmission of the WPT system is becoming more and more practical. Physical testing to assess the efficiency of the method will be performed in the coming years.

## REFERENCES


1. L. Fu , P. Cheng , Y. Gu , J. Chen , T. He, “Minimizing charging delay in wireless rechargeable sensor networks,” 2013 Proceedings IEEE INFOCOM, Turin, Italy, July 25 2013, pp. 2922–2930.
2. Guangjie Han, Aihua Qian, Jinfang Jiang, Ning Sun, Li Liu, “A grid-based joint routing and charging algorithm for industrial wireless rechargeable sensor networks,” Computer Networks, vol. 101, pp. 19-28, June 2016.
3. F. Zhao, H. Nie, and H. Chen. “Group buying spectrum auction algorithm for fractional frequency reuses cognitive cellular systems.” Ad Hoc Networks, vol. 58, pp. 239-246, April
4. F. Zhao, X. Sun, H. Chen, R. Bie, “Outage performance of relay- assisted primary and secondary transmissions in cognitive relay networks,” EURASIP Journal on Wireless Communications and Networking, 2014(1):60 , April 2014
5. F. Zhao, W. Wang, H. Chen and Q. Zhang, “Interference alignment and game-theoretic power allocation in MIMO heterogeneous sensor networks communications,” Signal Processing, vol. 126, pp. 173–179, 2016.
6. Q. Jia and W. K. S. Tang, “Consensus of multi-agents with event- based nonlinear coupling over time-varying digraphs,” IEEE Transactions on Circuits and Systems-II: Express Briefs, to be published, DOI: 10.1109/TCSII.2018.2790582
7. F. Zhao, B. Li, H. Chen, X. Lv, “Joint beamforming and power allocation for cognitive MIMO systems under imperfect CSI based on game theory,” Wireless Personal Communications, vol. 73, no. 3, pp. 679-694, Nov 2013.
8. Z. S. Zhao, X. Feng, Y. Y. Lin, F. Wei, S. K. Wang, T. L. Xiao, M.Y. Cao, Z. G. Hou, M. Tan, “Improved rao-blackwellized particle filter by particle swarm optimization,” Journal of Applied Mathematics, vol. 2013, Article No. 302170, 2013.
9. Xin Zhang and Xiu Zhang, “A binary artificial bee colony algorithm for constructing spanning trees in vehicular ad hoc networks,” Ad Hoc Networks, vol. 58, pp. 198-204, April 2017.
10. RunanGuo, Ziye Zhang, Xiaoping Liu, Chong Lin, “Existence, uniqueness, and exponential stability analysis for complex-valued memristor-based BAM neural networks with time delays,” Applied Mathematics and Computation, vol. 311, pp. 100-117, 2017.
11. Kumar, MJ&Baskaran, R (2017), Analyzing a Personalized Network System through NetFlow’, Institute of Integrative Omics and Applied Biotechnology (IIOAB), 7(7), pp. 1-7
12. Nancy, V. (2018). A Security for MANET Interruption Recognition & Preclusion approaches for Network Layer Attacks. International Journal of Applied Engineering Research, 13(12), 10702-10706.
13. Jan, Z., Azeem, N., &Zahoor, F. (2015, November). Digital watermarking using combination of Ranklets and wavelets. In2015 First International Conference on Anti-Cybercrime (ICACC)(pp. 1-5). IEEE.
14. G.O. Jijina, et.al, Design of Low Power and Area Efficient New Reconfigurable FIR Filter using PSM and Shift and Add Method, 2014, Research Journal of Applied Sciences, Engineering and Technology 8(24): 2416-2421, 2014 ISSN: 2040-7459


Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf

15. G.O. Jijina, et.al, Design of a novel reconfigurable FIR filter by Constant Shift Method Based on 4-Bit BCSE technique, January 2014International Journal of Applied Engineering Research 9(22):12689-12697.
16. Venkatesh, C., Madheswaran, M. Performance Analysis of Multiband OFDM System Over Ultra Wide Band Channels Using Kalman Filter. Wireless Pers Commun 68, 1121–1134 (2013).
17. 17.Madhavi, N., Madheswaran, M. Enhanced lifetime of heterogeneous wireless sensor network using stable election protocol with region-based energy-conscious sink movement. J Supercomput 76, 5715–5731 (2020).
18. Pattanaik, Balachandra, and S. Murugan. "Cascaded H-Bridge Seven Level Inverter using Carrier Phase Shifted PWM with Reduced DC sources." International Journal of MC Square Scientific Research 9, no. 3 (2017): 30-39.

Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0110970/16735744/020087_1_online.pdf